



Camera Specification:

3.1 M pixel resolution Microscope video camera live and still image capture

USB 2.0, support - PC Interface

1/2 inch, 3.1 M Pixels - Sensor

- Maximum Resolution

2048*1536

- Frame Rate

61dB - Dynamic Range

Electronic Rolling Snap(ERS),0.128~2000ms, ROI Auto & Manual - Exposure

8 fps at 2048*1536, 22 fps at 1024*768

- Color Rendering

Technique

Ultra Fine™ Color Engine

One Push ROI White Balance/ Manual Temp-Tint Adjustment - White Balance

Still Picture and Video - Capture Mode

From USB 2.0 Port - Power Source

White balance Automatic and Manu R-G-B

Exposure: Auto Exposure / Target / Time

Color: Color-Mono / Gamma / Saturation / Contrast

Misc: Flip-Horizontal / Flip-Vertical - Image Control

Frame Rate: Low / Medium / High

1 years Manufacturer's Warranty

The warranty covers manufacturing defects. Abuse or damage due to dropping is not covered.

Warning

This is the higher grade version that is USB 2.0 Compatible. USB 1.0 is significantly slower.



㈜리암솔루션

TEL:82-31-434-2710 FAX:82-70-4205-0352 Email: leamsol@leamsol.com WWW.LEAMSOL.COM

Distributor